



Schachtbauteile – DN 1000 nach DIN 4034 Teil 1 mit Muffe



HENTZSCHEL-BETON • Weinberge 9-11 • 04910 Elsterwerda

Wandstärke: 12 cm – max. Einbautiefe: 10,00 m.

			Gewicht kg	Art.-Nr.
Auflagering verschiebesicher				
	AR-V 625 / 40 mm		27	3200
	AR-V 625 / 60 mm		38	3201
	AR-V 625 / 80 mm		50	3202
	AR-V 625 / 100 mm		68	3203
	AR-V 625 / 120 mm		82	3199
Abdeckplatte – Muffe				
	AP-M 1000 / 200 Kl. D400 – 1 Öffn. 625		451	2354
Schachthals – Muffe				
	SH-M 1000 / 625 x 600	o. SE	600	2259
	SH-M 1000 / 625 x 600	m. SE	610	2260
	SH-M 1000 / 625 x 600	m. SB Form A	610	2261
	SH-M 1000 / 625 x 300	m. SE	450	3148
Schachtring – Muffe				
	SR-M 1000 / 250		290	2015
	SR-M 1000 / 500		555	2065
	SR-M 1000 / 750		850	2010
	SR-M 1000 / 1000		1045	2068
	SR-M 1000 / 250	m. SE	295	2016
	SR-M 1000 / 500	m. SE	565	2066
	SR-M 1000 / 750	m. SE	870	2013
	SR-M 1000 / 1000	m. SE	1065	2069
	SR-M 1000 / 250	m. SB Form A	295	2017
	SR-M 1000 / 500	m. SB Form A	565	2067
	SR-M 1000 / 750	m. SB Form A	870	2014
	SR-M 1000 / 1000	m. SB Form A	1065	2070
Fußauflagering - Muffe				
	FAR-M 1000 / 250		330	2270
Fugenabdichtung für Schachtringe mit Muffe DN 1000				
	Gleitringdichtung – vorgeschmiert			30351
	Lastausgleichelement			3025