







## Schachtbauteile – DN 1200 nach DIN 4034 Teil 2 mit Falz



HENTZSCHEL-BETON • Weinberge 9-11 • 04910 Elsterwerda

Wandstärke 9 cm – max. Einbautiefe: 10 m

		Gewicht kg	Art.-Nr.
<b>Abdeckplatte – Falz</b>			
	AP-F 1200 / 150 Kl. A15 – 1 Öffn. 625	290	2311
	AP-F 1200 / 200 Kl. B125 – 1 Öffn. 625	520	2306
	AP-F 1200 / 200 Kl. D400 – 1 Öffn. 625	525	2308
<b>Schachthals – Falz</b>			
	SH-F 1200 / 625 x 600 Kl. B125	550	2263
	SH-F 1200 / 625 x 600 Kl. B125 m. SE	560	2262
<b>Schachtring – Falz</b>			
	SR-F 1200 / 250	250	2021
	SR-F 1200 / 500	490	2071
	SR-F 1200 / 1000	960	2074
	SR-F 1200 / 250 m. SE	255	2022
	SR-F 1200 / 500 m. SE	500	2072
	SR-F 1200 / 1000 m. SE	970	2073
<b>Schachtring – Falz mit Boden</b>			
	SR-F 1200 / 500 m. Boden	785	2151
	SR-F 1200 / 500 m. Boden, SE	790	2152
	SR-F 1200 / 1000 m. Boden.	1325	21511
<b>Sickerring – Falz</b>			
	SiR-F 1200 / 500	470	2128
	SiR-F 1200 / 500 m. SE	485	2128E

### Zulagen

für 1 Kernbohrung + Dichtung DN 100 KG

für 1 Kernbohrung + Dichtung DN 150 KG