







## Schachtbauteile – DN 1500 nach DIN 4034 Teil 2 mit Falz



HENTZSCHEL-BETON • Weinberge 9-11 • 04910 Elsterwerda

Wandstärke: 9 cm – max. Einbautiefe: 5,00 m.

			Gewicht kg	Art.-Nr.
	<b>Abdeckplatte – Falz</b>			
	AP-F 1500 / 150 Kl. A15	– 1 Öffn. 625	590	2314
	AP-F 1500 / 200 Kl. B125	– 1 Öffn. 625	925	2310
	AP-F 1500 / 200 Kl. D400	– 1 Öffn. 625	950	2316
	<b>Schachthals – Falz</b>			
	SH-F 1500 / 625 x 600 Kl. B125		700	2268
	SH-F 1500 / 625 x 600 Kl. B125 m. SE		710	2267
	<b>Schachtring – Falz</b>			
	SR-F 1500 / 250		260	2031
	SR-F 1500 / 500		530	2081
	SR-F 1500 / 1000		1060	2083
	SR-F 1500 / 250	m. SE	265	2032
	SR-F 1500 / 500	m. SE	540	2082
	SR-F 1500 / 1000	m. SE	1070	2084
	<b>Schachtring – Falz mit Boden</b>			
	SR-F 1500 / 500	m. Boden	925	2161
	SR-F 1500 / 500	m. Boden, SE	930	2162
	SR-F 1500 / 1000	m. Boden	1435	21611
	<b>Sickerring – Falz</b>			
	SiR-F 1500 / 500		515	2129
	SiR-F 1500 / 500	m. SE	525	2129E

### Zulagen

für 1 Kernbohrung + Dichtung DN 100 KG  
für 1 Kernbohrung + Dichtung DN 150 KG