






Schachtbauteile – DN 2000 nach DIN 4034 Teil 2 mit Falz



HENTZSCHEL-BETON • Weinberge 9-11 • 04910 Elsterwerda

Wandstärke 9 cm – max. Einbautiefe: 5 m.

		Gewicht kg	Art.-Nr.
Abdeckplatte – Falz			
	AP-F 2000 / 200 Kl. B125 – 1 Öffn. 625	1630	2319
	AP-F 2000 / 200 Kl. D400 – 1 Öffn. 625	1725	2320
	AP-F 2000 / 200 Kl. D400 – 2 Öffn. 625	1595	2321
Schachthals – Falz mit zentrischer Öffnung			
	SH-F 2000 / 625 x 550 Kl. B125	940	2265
	SH-F 2000 / 625 x 550 Kl. B125 m. Öffn.	940	22651
	SH-F 2000 / 625 x 600 Kl. D400	1250	3004
	SH-F 2000 / 800 x 550	940	2264
Schachtring – Falz			
	SR-F 2000 / 500	740	2091
	SR-F 2000 / 750	1100	2095
	SR-F 2000 / 1000	1480	2097
	SR-F 2000 / 500 m. SE	745	2092
	SR-F 2000 / 1000 m. SE	1490	2098
Schachtring – Falz mit Boden			
	SR-F 2000 / 800 m. Boden	1770	2136
	SR-F 2000 / 1000 m. Boden	2150	21361
Sickerring – Falz			
	SiR-F 2000 / 500	725	2130
	SiR-F 2000 / 750	1080	2138
	SiR-F 2000 / 1000	1450	2139

Zulagen

für 1 Kernbohrung + Dichtung DN 100 KG

für 1 Kernbohrung + Dichtung DN 150 KG