






## Schachtbauteile – DN 2500 nach DIN 4034 Teil 2 mit Falz



HENTZSCHEL-BETON • Weinberge 9-11 • 04910 Elsterwerda

Wandstärke 10 cm – max. Einbautiefe: 5 m.

		Gewicht kg	Art.-Nr.
<b>Abdeckplatte – Falz</b>			
	AP-F 2500 / 200 Kl. D400 – 1 Öffn. 625	2575	2346
	AP-F 2500 / 200 Kl. D400 – 2 Öffn. 625	2410	2345
<b>Schachthals – Falz mit zentrischer Öffnung</b>			
	SH-F 2500 / 625 x 600 Kl. B125	1600	2520
	SH-F 2500 / 625 x 600 Kl. B125 m. Öffn.	1600	2519
	SH-F 2500 / 625 x 600 Kl. D400	1900	3003D
	SH-F 2500 / 800 x 600	1600	2521
<b>Schachtring – Falz</b>			
	SR-F 2500 / 500	980	2531
	SR-F 2500 / 750	1470	2533
	SR-F 2500 / 1000	1960	2548
<b>Schachtring – Falz mit Boden</b>			
	SR-F 2500 / 800 m. Boden	2700	2536
	SR-F 2500 / 1000 m. Boden	3400	2535
<b>Sickerring – Falz</b>			
	SiR-F 2500 / 750	1450	2534
	SiR-F 2500 / 1000	1930	2558

### Zulagen

für 1 Kernbohrung + Dichtung DN 100 KG  
für 1 Kernbohrung + Dichtung DN 150 KG