










Schachtbauteile – DN 800 nach DIN 4034 Teil 2 mit Falz

Wandstärke: 9 cm – max. Einbautiefe: 10,00 m.

| | | Gewicht kg | Art.-Nr. | Preis |
|---|--|---------------|----------|--------|
|  | Schachtabdeckung – nur begehbar | | | |
| | Mannlochdeckel AP-F 800 / 80 m. Öffn. und einliegenden Deckel | 110 | 3308 | 42,00 |
|  | 2-teiliger Deckel AP-F 800 / 60 | 100 | 3306 | 35,00 |
| | Abdeckplatte - Falz | | | |
| | AP-F 800 / 200 Kl. B125 – 1 Öffn. 625 | 175 | 2327 | 120,00 |
|  | AP-F 800 / 200 Kl. D400 – 1 Öffn. 625 | 180 | 2312 | 138,00 |
| | Schachthals – Falz | | | |
|  | SH-F 800 / 625 x 600 o. SE | 350 | 2251 | 40,00 |
| | SH-F 800 / 625 x 600 m. SE | 360 | 2252 | 51,00 |
| | Schachtring – Falz | | | |
|  | SR-F 800 / 250 | 155 | 2001 | 26,00 |
| | SR-F 800 / 500 | 310 | 2051 | 33,00 |
| | SR-F 800 / 1000 | 615 | 2055 | 54,00 |
|  | SR-F 800 / 250 m. SE | 160 | 2002 | 30,00 |
| | SR-F 800 / 500 m. SE | 320 | 2052 | 43,00 |
| | SR-F 800 / 1000 m. SE | 635 | 2054 | 74,00 |
| | SR-F 800 / 500 m. 1 Öffn. bruchrauh | 305 | 2101 | 40,00 |
|  | SR-F 800 / 500 m. 2 Öffn. bruchrauh | 295 | 2102 | 48,00 |
| | SR-F 800 / 500 m. 2 Öffn. bruchrauh 90° abgewinkelt | 295 | 2103 | 48,00 |
| | Schachtring – Falz mit Boden | | | |
|  | SR-F 800 / 500 m. Boden | 455 | 2131 | 58,00 |
| | SR-F 800 / 500 m. Boden, 1 Öffn. | 445 | 2134 | 65,00 |
| | SR-F 800 / 500 m. Boden, 2 Öffn. | 435 | 2135 | 72,00 |
|  | Sickerring – Falz | | | |
| | SiR-F 800 / 500 | 305 | 2126 | 40,00 |

Alle Preise in EUR zzgl. gesetzlicher USt., ab Werk Elsterwerda.